LIGHT-EMITTING DIODE

Patent Number:

JP6069546

Publication date:

1994-03-11

Inventor(s):

GOTOU HIROMASA; others: 01

Applicant(s):

ASAHI CHEM IND CO LTD

Requested Patent:

☐ <u>JP6069546</u>

Application Number: JP19920222627 19920821

Priority Number(s):

IPC Classification: HO1L33/00

EC Classification:

Equivalents:

Abstract

PURPOSE:To obtain an LED provided with a good light-emitting characteristic by using a wire bonding method when all electrodes for an element chip using an insulating substrate are connected to individual lead members.

CONSTITUTION:Individual chips are cut by using a dicing saw, one chip is taken out, the side of a reflection film 32 is die-bonded to a lead member 43 by using a Pb-Sn solder, electrodes for an ntype GaN layer 30 and an n-type Ga0.8In0.2N layer 41 are connected by 30mum phi Au wires 35 by using a wire bonding apparatus. Then, an i-type GaN layer electrode 27 is connected to a lead member 44 and an i-type Ga0.8In0.2N layer electrode 38 is connected to a lead member 43 respectively by 30mum phi Au wires 35 by using the wire bonding apparatus, and a manufactured light-emitting element 46 is sealed with a transparent epoxy resin. Consequently, all electrodes formed inside the same plane can be connected individually to lead members divided into the same number as the number of electrodes by using a wire bonding method. Thereby, an LED whose performance is stable can be supplied.

Data supplied from the esp@cenet database - 12